

Material Safety Data Sheet
 May be used to comply with
 OSHA's Hazard Communication Standard,
 29 CFR 1910. 1200. Standard must be
 consulted for specific requirements.

U.S. Department of Labor
 Occupational Safety and Health Administration
 (Non-Mandatory Form)
 Form Approved
 OMB No. 1218-0072

Section I - Product Name and Manufacturer

Identity (As appears on label): KIMODESK PREMIUM	Product Description (General Use): Plain Paper Copier Media - Polyester Film Based
Manufacturer's Name: KIMOTO TECH, INC.	Emergency Telephone, Contact Chemtrec: 1-800-424-9300 or (770) 748-2643
Address: 601 Canal Street P.O. Box 1783 Cedartown, Georgia 30125 (770) 748-2643	Date Prepared: January 5, 1998
This M.S.D.S. is based on information available at the time of publishing. This version supersedes any previously dated M.S.D.S. for this product.	

Section II - Hazardous Ingredients / Exposure Limits

Hazardous Components (Chemical Identity; Synonyms)	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (Optional)
Silicon Dioxide C.A.S. #7631-86-9 Synonyms: SiO ₂ , silica, silica gel, amorphous silica, synthetic silica	6 mg/m ³ (as powder)	10 mg/m ³ (as powder)		

There have been no known health effects related to the finished product.

Hazardous Materials Identification System Ratings:

Health Hazard: 0 Flammability Hazard: 1 Reactivity Hazard: 0 Personal Protection: N.A.

Section III - Physical / Chemical Characteristics

Boiling Point	N.A.	Specific Gravity (H ₂ O = 1)	Approx. N.A.
Vapor Pressure (mm Hg)	N.A.	Melting Point	Approx. 260° C
Vapor Density (Air = 1)	N.A.	Evaporation Rate (Butyl Acetate = 1)	N.A.

Solubility in Water: Insoluble

Appearance and Odor: White, opaque coated polyester film with no odor.

Section IV - Fire and Explosion Hazard Data

Flash Point (Method Used) 385° C	Flammable Limits	LEL N.A.	UEL N.A.
-------------------------------------	------------------	-------------	-------------

Extinguishing Media:

Water, Dry Chemical, or Foam

Special Fire Fighting Procedures:

Wear Self-Contained Breathing Apparatus as product may emit toxic vapors during thermal degradation. Avoid splattering of molten plastics with water system.

Unusual Fire and Explosion Hazards:

None.

N.A. = Not Applicable N.E. = Not Established

